

Local Supplier:

Anchor Data Systems (NI) Ltd

Belfast, N. Ireland, BT15 2GG Tel: +44 (0) 28 9074 0315
www.AnchorData.co.uk enquiries@AnchorData.co.uk

unitech

MS350

Cordless Scanner



MS350 Cordless Scanner Big Performance, Small Size!

One of the smallest and lightest high performance wireless linear imager scanners on the market, the MS350 is an extremely compact, lightweight, all-round robust device able to read 1D and 2D barcodes. Offering aggressive reading and decoding speeds, and a radio range up to 100m (Class I) from the base unit, the MS350 delivers the ultimate combination of performance and reliability for CCD barcode scanning applications, such as retail point of sale, healthcare, commercial and light industrial.

Premium Performance

The MS350's flexibility does not stop at its ability to scan a both 1D and 2D barcodes. With a long range scan engine and an increased depth of field, the MS350 boasts an impressive read rate of 300 scans per second, and can scan codes up to 10cm away. With no moving internal parts, its engine provides excellent reliability and performance, even when being dropped.

Never Miss a Scan

To give the ultimate piece of mind for users, the MS350 has an out of range alarm, adjustable good read audible indicators and a visible good read LED users can always be sure that barcodes are correctly captured first time, every time, even in noisy or poorly lit environments. Users will achieve an impressive 15,000 scans from a single charge. Benefit from its wireless technology connection, users will enjoy the freedom to roam wherever there is a need for scanning, by simply pairing with the base-station

Rugged and Reliable

Weighing in at just 180g, the MS350 is one of the lightest scanners in its class. Combined with a sleek, ergonomic design, the MS350 offers light and fatigue-free scanning, enhancing user comfort and work efficiency. It is designed to be durable and reliable: if the MS350 is accidentally dropped or knocked off a counter or desk, you can be assured it will keep on working perfectly as its drop test is up to 1.5m drops to concrete and comes with an IP42 protection rating. The MS350 delivers maximum reliability.

Quick and Easy to Set Up

Configuring the MS350 is easy: simply use Windows based software or scan a series of barcodes and you'll be up and running in no time. It also has a range of connectivity options, for flexible deployment in any environment, including USB, RS232 and keyboard wedge.

Features

- High performance Bluetooth Compatible Linear Imager Scanner
- Reads all common 1D and 2D barcodes
- Ergonomic, compact and stylish
- Rugged design (IP42) withstands multiple 1.5m drops to concrete
- Weighs less than 200g making it lightweight and comfortable to use
- Easy set up via USB and using Windows based software or barcodes
- Base unit supports RS232, keyboard wedge and USB
- Safety out of range alarm
- 3 years warranty

Local Supplier:

Anchor Data Systems (NI) Ltd

Unit 36 North City Business Centre,
Duncairn Gardens, Belfast, N. Ireland, BT15 2GG

Tel: +44 (0) 28 9074 0315 www.AnchorData.co.uk

enquiries@AnchorData.co.uk

MS350

Specifications

OPERATIONAL

| | |
|---------------------|--|
| Light Source | 630 nm Visible Red LED |
| Optical System | 2048 pixel CCD (Charge-coupled device) |
| Depth of Scan Field | 0~270mm (CODE 39, PSC=90%, 20mil) 0~180mm for 13mil 0~60mm for 5mil 5mm~50mm for 4mil |
| Scan Speed | 300 scans/sec |
| Resolution | 0.1mm (4mil) Code39, PCS=90% |
| Print Contrast | 30% or more |
| Scanning Angle | Front: 60° Rear: 60° Yaw: 70° |
| Radio Range | 100m (Class I) |
| Decode Capability | Auto-discriminates all standard barcodes and some 2D symbologies including PDF-417 and RSS code; Other symbologies can be ordered optionally |

MECHANICAL

| | |
|------------------|---------------------------------|
| Length | 187 mm |
| Width-handle | 35 mm |
| Width-head | 75 mm |
| Depth-handle | 33 mm |
| Weight | Less than 200g (with a battery) |
| Cradle interface | RS232, Keyboard wedge, USB |

ELECTRICAL

| | |
|-------------------|---------------------------------|
| Power Supply | Input voltage 5VDC \pm 10%VDC |
| Operating Current | 120mA @ 5VDC |
| Standby Current | 120mA @ 5VDC |
| Power Operating | 1073mW |
| Power Standby | 118mW |
| Light Level | Up to 45000 Lux |

PROGRAMMING

| | |
|--------------------|----------------------------------|
| Programming method | Manual (Reading special barcode) |
| Program upgrade | Enabled by built-in flash memory |
| Programmable | |

ENVIRONMENTAL

| | |
|-----------------------|--|
| Operating temperature | 0°C to 45°C (32°F to 113°F) |
| Storage temperature | -40°C to 60°C (-40°F to 140°F) |
| Relative humidity | 5% to 90% relative humidity (non-condensing) |
| Drop test | 1.5m drop onto concrete |
| IP rating | IP42 |
| Safety approval | UL, FCC, CLASS A, CE CLASS A |



Local Supplier:

Anchor Data Systems (NI) Ltd

Unit 36 North City Business Centre,
Duncairn Gardens, Belfast, N. Ireland, BT15 2GG

Tel: +44 (0) 28 9074 0315 www.AnchorData.co.uk

enquiries@AnchorData.co.uk

Specifications subject to change without notice. Copyright Unitech Europe. All rights reserved.
Unitech is a registered trademark of Unitech Electronics Co., Ltd. All trademarks are the property of their respective owners.

ORACLE PARTNER



MS350-08V2

unitech

Unitech EUROPE, EMEA HEAD OFFICE Kapitein Hatterasstraat 19 5015 BB Tilburg the Netherlands tel: +31.13.460 9292 info@unitech-europe.com WWW.Unitech-EUROPE.COM

