

Z-6170

Hands-free Omnidirectional Laser Scanner (Preliminary)



- Support both omnidirectional and single-line scanning
- Aggressive scanning performance
- Proprietary Z-SCAN⁺ technology
- Ergonomic and rugged design
- Flexible communications

Elegant and functional, the newly-designed Z-6170 leads the trend and is to enhance retail stores to the next level at an affordable price. Its unique outlook fits perfectly into places like bookstore, boutique and anywhere delicacy is a must.

Equipped with a speaker but a buzzer, its adjustable tone and volume work well in either quite or noisy environments. With a standard EAS antenna, the Z-6170 has 20-line omnidirectional laser beams reading at 1200 scans per second, decoding most popular 1D barcodes. Able to be tilted forward or backward to suit user's special applications, the Z-6170 is your dreaming partner of utility and beauty!

Local Supplier:

Anchor Data Systems (NI) Ltd

Unit 36 North City Business Centre
Duncairn Gardens, Belfast, BT15 2GG

Tel: 028 9074 0315 Fax: 028 9035 1531

Email: enquiries@AnchorData.co.uk Web: www.AnchorData.co.uk

OPERATIONAL

Light Source	650 nm visible laser diode (VLD)
Depth of Field	0 – 216 mm (UPC/EAN 100%, PCS=90%)
Scan Pattern	5 directions of scan field
Scan Rate	1,200 scans per second (omnidirectional)
Number of Scan Lines	20
Minimum Bar Width	5 mil @ PCS=90%
Print Contrast	30% @ UPC/EAN 100%
Indicators (LED)	Two-color LED (green, red)
Beeper Operation	Programmable tone & volume
System Interfaces	Keyboard wedge, RS-232, HID USB

PHYSICAL

Dimensions	(L)118.0 × (W)100.0 × (H)165.1 mm
Weight	360 g (without cable)
Cable	Standard 2.0M straight

POWER

Input Voltage	5 VDC ±10%
Power Consumption	1.35 watts
Operating Current	270 mA (typical); 350 mA (peak)

REGULATORY

Laser Class	CDRH Class IIa; IEC 60825-1: Class 1
EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI

ENVIRONMENTAL

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	5% – 90% RH (no dewing allowed)
Light Levels	Up to 4,000 Lux (fluorescence)
Drop Durability	Designed to withstand 1.0M drops



Product availability and specifications depend on territory market strategy; all are subjects to change without prior notice.
ZEBEX is the trademark of ZEBEX INDUSTRIES INC., all rights reserved.

ZEBEX
www.zebex.com